



Pressure injected foam insulation

Self closing doors

Fan assisted cooling

Solid construction

Automatic defrost with self-evaporating drip tray

Digital temperature display

Double-glazed glass door

Fully adjustable shelves every 11mm

Interior illumination

Optional LED lights

Optional 840mm and 865mm heights

Optional heated triple-glazed doors

Technical Specifications

MODEL	HUS-C1-HY single door undercounter chiller	MODEL	HUS-C2-HY double door undercounter chiller	MODEL	HUS-C3-HY triple door undercounter chiller
CAPACITY		CAPACITY		CAPACITY	
Nett Total/Litres	116	Nett Total/Litres	184	Nett Total/Litres	289
PERFORMANCE		PERFORMANCE		PERFORMANCE	
Power Input watts	125	Power Input watts	155	Power Input watts	225
Energy Consumption Kwh/24h	1.3	Energy Consumption Kwh/24h	1.8	Energy Consumption Kwh/24h	2.3
Temperature Range	0°-10°C	Temperature Range	0°-10°C	Temperature Range	0°-10°C
FEATURES		FEATURES		FEATURES	
Temp. Control	Electronic	Temp. Control	Electronic	Temp. Control	Electronic
Shelves	2	Shelves	4	Shelves	6
DIMENSIONS		DIMENSIONS		DIMENSIONS	
Net HxWxD	900x595x520	Net HxWxD	900x900x520	Net HxWxD	900x1350x520
Weight Nett	46.2	Weight Nett	62.4	Weight Nett	88.6
Loading 40'HQ	144	Loading 40'HQ	100	Loading 40'HQ	66

© 2011 Husky. Husky reserve the right to change specifications at any time without notice.